



# SOLARIF

RISK MANAGEMENT

Certificate number: **PV 20190503000**

Certificate holder: **Vikram Solar Ltd.**

Valid from: **03.05.2019**

Expires on: **03.05.2020**

Solarif Risk Management B.V. declares, after a thorough risk assessment of amongst others the production lines, financial strength, environmental and labor conditions, that the modules mentioned below from the **Vikram Solar Ltd.** factory located at **Falta-SEZ, 24 Parganas (South), Kolkata, 743504 West Bengal, India**, are approved.

The certificate is valid from **03.05.2019** until **03.05.2020** and as long as the company is not insolvent.

This certificate enables clients of **Vikram Solar Ltd.** to purchase Solarif's unique inherent defect coverage in addition to Solarif's Operational all risk insurance, supporting and backing-up the manufacturer's warranty in case of inherent defect.

This insurance is exclusively available through Solarif Insurance.

For more information or a quotation, please contact us at +31 (0) 26 711 5050, by email [support@solarif.com](mailto:support@solarif.com) or visit our website [www.solarif.com](http://www.solarif.com).

Date: **04.11.2019**

Xander Vendrig / Manager Risk Management  
Solarif Risk Management BV



CERTIFICATE



# SOLARIF

RISK MANAGEMENT

Certificate number: **PV 20190503000**

Certificate holder: **Vikram Solar Ltd.**

Valid from: **03.05.2019**

Expires on: **03.05.2020**

## APPROVED MONO-CRYSTALLINE MODULES

<i>Model</i>	<i>Max. Power (Wp)</i>	<i>Tolerance</i>	<i>Euro. Efficiency</i>	<i>Number and size of cell</i>
SOMERA VSM.72.XXX.03.04	310-380	±3	1000	72/ 156mm x 156mm
SOMERA VSM.60.XXX.03.04	260-315	±3	1000	60/ 156mm x 156mm
SOMERA VSM.54.XXX.03.04	235-285	±3	1000	54/ 156mm x 156mm
SOMERA VSM.48.XXX.03.04	210-255	±3	1000	48/ 156mm x 156mm
SOMERA VSM.36.XXX.03.04	155-190	±3	1000	36/ 156mm x 156mm
SOMERA VSMB.72.XXX.03.04	310-380	±3	1000	72/ 156mm x 156mm
SOMERA VSMB.60.XXX.03.04	260-315	±3	1000	60/ 156mm x 156mm
SOMERA VSMB.54.XXX.03.04	235-285	±3	1000	54/ 156mm x 156mm
SOMERA VSMB.48.XXX.03.04	210-255	±3	1000	48/ 156mm x 156mm
SOMERA VSMB.36.XXX.03.04	155-190	±3	1000	36/ 156mm x 156mm
SOMERA VSMS.72.XXX.03.04	310-380	±3	1000	72/ 156mm x 156mm
SOMERA VSMSB.72.XXX.03.04	310-380	±3	1000	72/ 156mm x 156mm
SOMERA VSMS.60.XXX.03.04	260-315	±3	1000	60/ 156mm x 156mm
SOMERA VSMSB.60.XXX.03.04	260-315	±3	1000	60/ 156mm x 156mm

## APPROVED MONO-CUT MODULES

<i>Model</i>	<i>Max. Power (Wp)</i>	<i>Tolerance</i>	<i>Euro. Efficiency</i>	<i>Number and size of cell</i>
SOMERA VSMH.72.XXX.03.04	325-400	±3	1000	72/ 156mm x 156mm
SOMERA VSMHB.72.XXX.03.04	325-400	±3	1000	72/ 156mm x 156mm
SOMERA VSMH.60.XXX.03.04	270-330	±3	1000	60/ 156mm x 156mm
SOMERA VSMHB.60.XXX.03.04	270-330	±3	1000	60/ 156mm x 156mm





# SOLARIF

RISK MANAGEMENT

APPROVED POLY-CRYSTALLINE MODULES				
<i>Model</i>	<i>Max. Power (Wp)</i>	<i>Tolerance</i>	<i>Euro. Efficiency</i>	<i>Number and size of cell</i>
ELDORA VSP.72.XXX.03.04	285-350	±3	1000	72/ 156mm x 156mm
ELDORA VSP.60.XXX.03.04	235-290	±3	1000	60/ 156mm x 156mm
ELDORA VSP.54.XXX.03.04	215-265	±3	1000	54/ 156mm x 156mm
ELDORA VSP.48.XXX.03.04	190-235	±3	1000	48/ 156mm x 156mm
ELDORA VSP.36.XXX.03.04	145-175	±3	1000	36/ 156mm x 156mm
ELDORA.VSPB.72.XXX.03.04	285-350	±3	1000	72/ 156mm x 156mm
ELDORA VSPB.60.XXX.03.04	235-290	±3	1000	60/ 156mm x 156mm
ELDORA VSPB.54.XXX.03.04	215-265	±3	1000	54/ 156mm x 156mm
ELDORA VSPB.48.XXX.03.04	190-235	±3	1000	48/ 156mm x 156mm
ELDORA VSPB.36.XXX.03.04	145-175	±3	1000	36/ 156mm x 156mm
ELDORA VSPS.72.XXX.03.04	285-350	±3	1000	72/ 156mm x 156mm
ELDORA VSPS.60.XXX.03.04	240-293	±3	1000	60/ 156mm x 156mm
ELDORA VSPSB.72.XXX.03.04	285-350	±3	1000	72/ 156mm x 156mm
ELDORA VSPSB.60.XXX.03.04	240-293	±3	1000	60/ 156mm x 156mm
ELDORA VSP.72.XXX.03	275-335	±3	1000	72/ 156mm x 156mm
ELDORA VSP.60.XXX.03	228-279	±3	1000	60/ 156mm x 156mm
ELDORA VSP.54.XXX.03	205-250	±3	1000	54/ 156mm x 156mm
ELDORA VSP.48.XXX.03	182-223	±3	1000	48/ 156mm x 156mm
ELDORA VSP.36.XXX.03	137-168	±3	1000	36/ 156mm x 156mm
ELDORA VSPB.72.XXX.03	275-335	±3	1000	72/ 156mm x 156mm
ELDORA VSPB.60.XXX.03	228-279	±3	1000	60/ 156mm x 156mm
ELDORA VSPB.54.XXX.03	205-250	±3	1000	54/ 156mm x 156mm
ELDORA VSPB.48.XXX.03	182-223	±3	1000	48/ 156mm x 156mm
ELDORA VSPB.36.XXX.03	137-168	±3	1000	36/ 156mm x 156mm
ELDORA VSP.60.XXX.03.01	228-279	±3	1000	60/ 156mm x 156mm
ELDORA VSP.54.XXX.03.01	205-250	±3	1000	54/ 156mm x 156mm
ELDORA VSP.48.XXX.03.01	182-223	±3	1000	48/ 156mm x 156mm
ELDORA VSP.36.XXX.03.01	137-168	±3	1000	36/ 156mm x 156mm
ELDORA VSP.72.XXX.04	300-365	±3	1000	72/ 156mm x 156mm
ELDORA VSP.60.XXX.04	250-305	±3	1000	60/ 156mm x 156mm
ELDORA VSP.54.XXX.04	225-275	±3	1000	54/ 156mm x 156mm
ELDORA VSP.48.XXX.04	200-245	±3	1000	48/ 156mm x 156mm
ELDORA VSP.36.XXX.04	150-185	±3	1000	36/ 156mm x 156mm
ELDORA VSPB.72.XXX.04	300-365	±3	1000	72/ 156mm x 156mm
ELDORA VSPB.60.XXX.04	250-305	±3	1000	60/ 156mm x 156mm
ELDORA VSPB.54.XXX.04	225-275	±3	1000	54/ 156mm x 156mm

Solarif Risk Management BV

Mr. B.M. Teldersstraat 11 | 6842 CT Arnhem | PO Box 4192 | 6803 ED Arnhem | The Netherlands  
T. +31 (0)26 711 5050 | info@solarif.com | www.solarif.com | IBAN NL93RABO0302073744  
COC 09193608 | VAT NL820465148B01





# SOLARIF

RISK MANAGEMENT

ELDORA VSPB.48.XXX.04	200-245	±3	1000	48/ 156mm x 156mm
ELDORA VSPB.36.XXX.04	150-185	±3	1000	36/ 156mm x 156mm

## APPROVED POLY-CUT MODULES

<i>Model</i>	<i>Max. Power (Wp)</i>	<i>Tolerance</i>	<i>Euro. Efficiency</i>	<i>Number and size of cell</i>
ELDORA VSPH.72.XXX.03.04	295-360	±3	1000	72/ 156mm x 156mm
ELDORA VSPHB.72.XXX.03.04	295-360	±3	1000	72/ 156mm x 156mm
ELDORA VSPH.60.XXX.03.04	245-300	±3	1000	60/ 156mm x 156mm
ELDORA VSPHB.60.XXX.03.04	245-300	±3	1000	60/ 156mm x 156mm
ELDORA VSPH.72.XXX.05	295-360	±3	1000	72/ 156mm x 156mm
ELDORA VSPHB.72.XXX.05	295-360	±3	1000	72/ 156mm x 156mm
ELDORA VSPH.60.XXX.05	245-300	±3	1000	60/ 156mm x 156mm
ELDORA VSPHB.60.XXX.05	245-300	±3	1000	60/ 156mm x 156mm

